

New Zealand Trailer Yacht Ratings

Current from August 2011 Version 2

| Boat Type | NZTYA Rating | SRI | Division (recommended) | Minimum Motor Size (HP) <small>Clarification check to Rule 13 YNZ Safety Regulations Part V</small> |
|-------------------|---------------------|------------|-------------------------------|--|
| Aquarius 22 | 0.760 | 0.860 | B | 5.5 |
| Aquarius 8M | 0.826 | 0.860 | B | 6.6 |
| Austral 8 | 0.920 | | A | 6.6 |
| Beachcomber 6.5 | 0.733 | 0.530 | C | 5.3 |
| Beale 780 | 0.860 | | A | 6.4 |
| Birdsall 22 | 0.724 | | C | 5.5 |
| Bonito 580 | 0.678 | | C | 4.8 |
| Brooke 25 | 0.790 | 1.160 | B | 6.3 |
| Bull 7000 | 0.915 | 0.680 | A | 5.7 |
| Careel 18 | 0.653 | | C | 4.5 |
| Caribou 17 | 0.680 | | C | 4.3 |
| Caribou 18 | 0.699 | | C | 4.5 |
| Caribou 20 | 0.757 | 0.450 | C | 5.0 |
| Catalina 7 | 0.795 | | B | 5.7 |
| Cherry 16 | 0.648 | | C | 4.0 |
| Chubb 770 | 0.935 | 1.390 | A | 6.3 |
| Cirrus 6000 | 0.745 | 0.400 | C | 4.9 |
| Coronet 20 | 0.723 | 0.900 | C | 5.0 |
| Coronet 25 | 0.798 | | B | 6.3 |
| Coxhead | 0.815 | | B | |
| Cresta Craft 5.75 | 0.678 | | C | 4.7 |

| Boat Type | NZTYA Rating | SRI | Division (recommended) | Minimum Motor Size (HP) Clarification check to Rule 13 YNZ Safety Regulations Part V |
|---|---------------------------------------|------------|-------------------------------|---|
| Dahl 4.88 | 0.689 | | C | 4.0 |
| Dahl 780 | 0.852 | | B | 6.4 |
| Dale 7.6 | 0.850 | | B | 6.2 |
| Dale 760 (Bernz) | 0.990 | | A | 6.2 |
| Dale 8.3 | 0.960 | | A | 6.8 |
| Dancer 5.8 | 0.667 | 0.960 | C | 4.8 |
| Davidson 16 | 0.667 | | C | 4.0 |
| Davidson 20 | 0.686 | 0.950 | C | 5.0 |
| Davidson 26 | 0.860 | | A | 6.5 |
| Denison 780 | 0.816 | | B | 6.4 |
| Dibley 650 | 0.980 | 1.095 | A | 5.3 |
| DiDi 26 | Yet to be approved as a Trailer Yacht | | | 6.5 |
| Eagle 8 (Dibley8) | 0.985 | | A | 6.6 |
| Eclipse 750 (Revised Trojan 750) | 0.828 Provisional | | B | 6.2 |
| Elder 680 | 0.929 | | A | 5.6 |
| Elder 680 Mod (Dagger Board Keel) | 1.020 | 0.731 | A | 6.4 |
| Elder 680 Mod (Swing keel) | 0.990 | 0.859 | A | 6.4 |
| Elder 7.6 | 0.862 | | A | 6.2 |
| Elliott 5.9 | 0.895 | 1.608 | A | 4.8 |
| Elliott 6.5 | 0.935 | 1.700 | A | 5.3 |
| Elliott 6.5 Mod (includes Mast head Spinnaker / gennaker, Prod, Altered Bulb) | 0.945 | | A | 5.3 |
| Elliott 6.5 Mod (T3905) | 0.975 | | A | 5.3 |

| Boat Type | NZTYA Rating | SRI | Division (recommended) | Minimum Motor Size (HP) Clarification check to Rule 13 YNZ Safety Regulations Part V |
|----------------------------|-----------------------------|------------|-------------------------------|---|
| Elliott 7 | 0.941 | | A | 5.7 |
| Elliott 7 Mod. T4047 | 0.972 Provisional | | A | 5.7 |
| Elliott 7.4 (Bulb Keel) | 0.895 | | A | 6.1 |
| Elliott 7.4 (Winged Keel) | 0.890 | 3.180 | A | 6.1 |
| Elliott 7.8 | 0.950 | 1.220 | A | 6.4 |
| Elloitt 7.8 Mod (T4052) | 0.985 | | A | 6.4 |
| Elloitt 7.8 OZ Mod (T3949) | 1.010 Provisional | | A | 6.4 |
| Emeny 8 | 0.860 | | A | 6.6 |
| Empress 20 | 0.747 | | C | 5.0 |
| Eun Mara Canoe Yawl 6.0 | 0.580 | | C | 4.9 |
| Explorer 770 | 0.850 | 0.440 | B | 6.3 |
| Express 780 | 0.856 | | B | 6.4 |
| Farr 5000 | 0.647 | 0.600 | C | 4.1 |
| Farr 6000 | 0.745 | 0.650 | C | 4.9 |
| Farr 6000 Mod (with Genoa) | 0.760 | | C | 4.9 |
| Farr 740 Sport | 0.865 | 1.070 | A | 6.0 |
| Farr 7500 | 0.825 | 1.230 | B | 6.2 |
| Fiona Marie | 0.815 | | B | 5.3 |
| Flush Poker (20) | 0.830 | 1.010 | B | 5.0 |
| Freeway 780 | 0.861 | | A | 6.4 |
| Fun 780 | 0.826 | | B | 6.4 |
| Gazelle Mk1 | 0.820 | | B | 6.5 |

| Boat Type | NZTYA Rating | SRI | Division (recommended) | Minimum Motor Size (HP) Clarification check to Rule 13 YNZ Safety Regulations Part V |
|----------------------------|-----------------------------|------------|-------------------------------|---|
| Gazelle Mk1 Mod | 0.820 | | B | 6.5 |
| Gazelle Mk11 | 0.850 | | B | 6.5 |
| Given 780 | 0.826 | | B | 6.4 |
| Harness 16 | 0.785 | | B | 4.0 |
| Hartley 14 | 0.602 | | C | 3.5 |
| Hartley 16 | 0.710 | 0.110 | C | 4.0 |
| Hartley 18 | 0.700 | 0.830 | C | 4.5 |
| Hartley 21 | 0.723 | 0.846 | C | 5.3 |
| Hislop 7.5 | 0.794 | 0.210 | B | 6.2 |
| Hislop Special (8.7M) | 0.934 | | A | 7.1 |
| Honey 27 | 0.826 | | B | 6.8 |
| Hot Pot 7.7 | 0.825 | | B | 6.3 |
| Joker 6.7 | 0.812 | 0.878 | B | 5.5 |
| Joker 820 | 0.855 | 1.707 | B | 6.7 |
| Kestrel 18 | 0.694 | 0.260 | C | 4.5 |
| Lambert 7.8 | 0.891 | | A | 6.4 |
| Leach 8m | 0.905 Provisional | | A | 6.6 |
| Lidgard 18 | 0.745 | | C | 4.5 |
| Lightening 7.5 Mod (T3978) | 0.990 | 0.680 | A | 6.2 |
| Lightening 7.5 | 0.915 | 0.859 | A | 6.2 |
| Lloyd 6.9 | 0.783 | 0.850 | B | 5.7 |
| MacGregor 26 WB | 0.820 | | B | 6.5 |

| Boat Type | NZTYA Rating | SRI | Division (recommended) | Minimum Motor Size (HP) Clarification check to Rule 13 YNZ Safety Regulations Part V |
|------------------|---------------------|------------|-------------------------------|---|
| Magnum 20 | 0.724 | | C | 5.0 |
| Mallard 22 | 0.748 | | C | 5.5 |
| Maverick 6.9 | 0.860 | | A | 5.7 |
| McKenzie 780 | 0.955 | | A | 6.4 |
| Merlin 20 | 0.703 | 0.480 | C | 5.0 |
| Midnight 21 | 0.750 | | C | 5.3 |
| Minetun 6.8 | 0.722 | 1.090 | C | 5.6 |
| Mirador 6.1 | 0.684 | | C | 5.0 |
| Mirador 680 | 0.810 | | B | 5.6 |
| Monarch/Pacer 17 | 0.646 | 0.630 | C | 4.3 |
| Moonraker 16 | 0.653 | | C | 4.0 |
| Moonraker 18 | 0.687 | 1.232 | C | 4.5 |
| Moonraker 19 | 0.680 | | B | 4.7 |
| Moonraker 20 | 0.765 | | B | 5.0 |
| Moonraker 23 | 0.798 | | B | 5.8 |
| Moonraker 26 | 0.816 | | B | 6.5 |
| Moonraker 8M | 0.826 | | B | 6.6 |
| Morgan 7.4 | 0.919 | 0.930 | A | 6.1 |
| Murchie 595 | 0.776 | | B | 4.9 |
| Nimbus | 0.826 | | B | |
| Noeleada 7.32 | 0.759 | | C | 6.0 |
| Noelex 22 | 0.811 | 1.180 | B | 5.5 |

| Boat Type | NZTYA Rating | SRI | Division (recommended) | Minimum Motor Size (HP) <small>Clarification check to Rule 13 YNZ Safety Regulations Part V</small> |
|--------------------|---------------------|------------|-------------------------------|--|
| Noelex 25 | 0.845 | 1.040 | B | 6.3 |
| Nordic | 0.602 | | C | |
| Omega 7 | 0.765 | | B | 5.7 |
| Orchard | 0.808 | | B | |
| Pacer 7.4 | 0.823 | | B | 6.1 |
| Pegasus 840 | 1.045 | 0.980 | A | 6.9 |
| Quicksilver 16 | 0.664 | 0.370 | C | 4.0 |
| Quintet 5.0 | 0.684 | | C | 4.1 |
| Quintet 6.0 | 0.765 | | B | 4.9 |
| Quintet 7 | 0.824 | | B | 5.7 |
| Quintet 780 | 0.825 | 1.150 | B | 6.4 |
| Redwing 6.0 | 0.709 | | C | 4.9 |
| Rendle 6.7 | 0.786 | | B | 5.5 |
| Retriver 6.7 | 0.758 | | C | 5.5 |
| Ross 650 (Bulb) | 0.840 | 1.017 | B | 5.3 |
| Ross 650 (No Bulb) | 0.825 | 0.790 | B | 5.3 |
| Ross 780 | 0.933 | 1.450 | A | 6.4 |
| Rover 6.8 | 0.756 | | C | 5.6 |
| Sabre 20 | 0.700 | 0.690 | C | 5.0 |
| Sabre 22 | 0.740 | | C | 5.5 |
| Sabre 25 | 0.816 | | B | 6.3 |
| Sandman 20 | 0.724 | | C | 5.0 |

| Boat Type | NZTYA Rating | SRI | Division (recommended) | Minimum Motor Size (HP) Clarification check to Rule 13 YNZ Safety Regulations Part V |
|------------------------|---------------------|------------|-------------------------------|---|
| Sandpiper 20 | 0.746 | | C | 5.0 |
| Scintillation 7.8 | 0.825 | 1.375 | B | 6.4 |
| Scorpio 25 | 0.826 | | B | 6.3 |
| Sigrid 6.3 | 0.804 | | B | 5.2 |
| Sonata 24 | 0.724 | | C | 6.0 |
| Tasman 20 | 0.737 | 1.070 | C | 5.0 |
| Tenspeed | 0.880 | | A | |
| Thompson 650 | 1.060 | | A | 5.3 |
| Thompson 7M | 0.950 | | A | 5.7 |
| Thompson 8m | 1.120 | 1.720 | A | 6.6 |
| Thompson 8m SC | 1.025 | | A | 6.6 |
| Trojan 750 | 0.815 | 1.270 | B | 6.2 |
| Trojan 750 Mk11 (Bulb) | 0.825 | | B | 6.2 |
| Tropic 4.6 | 0.622 | | C | 3.8 |
| Unleashed 7M | 0.993 | | A | 5.7 |
| Van Dieman 5.6 | 0.705 | | C | 4.6 |
| Variant 22 | 0.687 | | C | 5.5 |
| Variant 7.7 | 0.826 | | B | 6.3 |
| Ventura 20 | 0.677 | | C | 5.0 |
| Venura 17 | 0.646 | | C | 4.3 |
| Wagstaff 22 (T1958) | 0.758 | | C | 5.5 |
| Wagstaff 660 | 0.750 | | C | 5.4 |

| Boat Type | NZTYA Rating | SRI | Division (recommended) | Minimum Motor Size (HP) <small>Clarification check to Rule 13 YNZ Safety Regulations Part V</small> |
|---------------------------|-----------------------------|------------|-------------------------------|--|
| Webster 5.4 | 0.652 | | C | 4.4 |
| Whiting 16 | 0.650 | 0.110 | C | 4.0 |
| Whiting 22 | 0.785 | 1.540 | B | 5.5 |
| Williams 6 | 0.855 | 0.640 | B | 4.9 |
| Williams 7 | 0.860 | | A | 5.7 |
| Witchcraft | 0.810 | 1.390 | B | |
| XS Eight | 0.895 | | A | 6.6 |
| Young 5.2 | 0.722 | | C | 4.3 |
| Young 5.7 | 0.709 | 0.328 | C | 4.7 |
| Young 6.0 WB | 0.792 | | B | 4.9 |
| Young 6.7 WB | 0.818 | 1.120 | B | 5.5 |
| Young 7.0 | 0.860 | | A | 5.7 |
| Young 7.8 WB | 0.860 | 0.680 | A | 6.4 |
| Young 7.8 WB - Modified | 0.890 | | A | 6.4 |
| Young 77 | 0.885 | 1.870 | A | 6.6 |
| Young 780 Rocket | 0.895 | | A | 6.4 |
| Young 780 Rocket Modified | 0.905 Provisional | | A | 6.4 |
| Z5 | 0.780 | | B | |